



781.767.4511 | www.EastexProducts.com

Product Specification Sheet

Part # 30000

Product Slip-Not 12000

Description

Slip-Not 12000 is a phthalate/DEHP free PVC coated woven polyester. It is embossed with a unique pebble anti-migration pattern that gives it non-slip grip qualities in both wet and dry conditions.

Key Features

- Washable with soap and water
- Fire Resistant (CAL 117)
- Abrasion Resistant
- Fluid Proof
- Non-Slip
- Phthalate/DE Free
- Embossing: Fine, High Pebble

Applications

- Luggage, Bags, Backpacks, Tents
- Military, Law Enforcement, Tactical
- Orthopedic, Support Surface, Patient Transfer
- Wheelchair Covers
- Safety
- Industrial

Color

Black

Width

56" (54" Useable Fabric)

Length

40 yd

Thickness

0.7mm

Weight

21 oz/sq yd

Composition

100% Polyvinyl Chloride (PVC) (Phthalate/DEHP Free) Coated 100% Polyester Woven Backer

Test/Property	Method	Unit/Standard	Results
Tensile Strength	ASTM D5034	kg	Warp: 29.8
	Grab Method		Weft: 39.7
Tearing Strength	ASTM D1424	gr	Warp: 1532
			Weft: 1435
Wear/Abrasion Resistance	Taber Test Revolutions	H18 Grit Wheel 500 gm weight	Revolutions: 10,430

Test/Property	Method	Unit/Standard	Results
Fire Resistance	CAL117-SecE Fire Regulations	Did not ignite	Pass
Cold Crack	ASTM D 2136	Conditioned:-40C for 6 hours	Pass
Colorfastness to Crocking	AATCC 8	Dry Procedure Wet Procedure	No change or staining No change or staining
Heat Test	Samples Placed in Oven	Conditioned: 105 C for 6 hours	No Change to coating or fabric