

## **Product Specification Sheet**

Part #30001

781.767.4511 | www.EastexProducts.com

Product	Slip-Not 12000 Dots
Description	Slip-Not/12000 is a phthalate/DEHP free PVC (Polyvinyl Chloride) coated woven polyester. It is embossed with a unique DOT anti-migration pattern that gives it enhanced non-slip grip qualities in both wet and dry conditions.
Key Features	<ul> <li>Phthalate/DEHP Free</li> <li>Washable with Soap and Water</li> <li>Fire Resistant (CAL 117)</li> <li>Abrasion Resistant</li> <li>Fluid Proof</li> <li>Non-Slip</li> </ul>
Applications	<ul> <li>Luggage, Bags, Backpacks, Tents</li> <li>Military, Law Enforcement, Tactical</li> <li>Orthopedic, Support Surface, Patient Transfer, Wheelchair Covers</li> <li>Safety</li> <li>Industrial</li> </ul>
Color	Black
Width	54"
Length	40 yd
Thickness	0.85 mm
Weight	23 oz sq/yd
Composition	100% Black Polyester Knit Fabric

Test/Property	Method	Unit/Standard	Results
To poile Strong atta	ASTM D5034	kg	Warp: 31.2
Tensile Strength	Grab Method		Weft: 43.3
	ASTM D1424	gr	Warp: 1740
Tearing Strength	Pendulum Method		Weft: 1660
Magr/Abrasian Desistance	e Taber Test Revolutions	H18 Grit Wheel	Revolutions: 10,430
Wear/Abrasion Resistance		500 gm weight	
Fire Resistance	CAL117-SecE Fire Regulations	Did not ignite	Pass

Test/Property	Method	Unit/Standard	Results
Cold Crack	ASTM D 2136	Conditioned: -40C for 6 hours	Pass
Colorfastness to Crocking	AATCC 8	Dry Procedure Wet Procedure	No change or staining No change or staining
Heat Test	Samples Placed in Oven	Conditioned: 105 C for 6 hours	No Change to coating or fabric