

## **Product Specification Sheet**

Part # 30005

781.767.4511 | www.EastexProducts.com

Product	Slip-Not Pebble 12000
Description	Slip-Not is a unique fabric that holds up strongly to wear and abrasion while also offering grip and non-skid in both wet and dry conditions.
Key Features Applications	<ul> <li>Washable with Soap and Water</li> <li>Fire Resistant (CAL 117)</li> <li>Abrasion Resistant</li> <li>Fluid Proof</li> <li>Non-Slip</li> <li>Embossing: Fine, High Pebble</li> <li>Luggage, Bags, Backpacks</li> <li>Tents</li> <li>Military</li> <li>Law Enforcement, Tactical</li> <li>Industrial</li> <li>Wheelchair Covers</li> <li>Safety</li> </ul>
Color	Coyote
Width	54"
Length	40yd
Thickness	.7mm
Weight	36 oz/yd
Composition	100% Polyester Woven Fabric

Method	Unit/Standard	Results
ASTM D5034	kg	Warp: 31.2
Grab Method		Weft: 43.3
ASTM D1424		Warp: 1740
Pendulum Method	gr	Weft: 1660
e Taber Test Revolutions	H18 Grit Wheel	Revolutions: 10,430
	500 gm weight	REVOIUTIONS, 10,430
CAL117-SecE Fire Regulations	Did not ignite	Pass
	ASTM D5034 Grab Method ASTM D1424 Pendulum Method Taber Test Revolutions CAL117-SecE Fire	ASTM D5034 kg Grab Method gr Pendulum Method gr Taber Test Revolutions H18 Grit Wheel 500 gm weight CAL117-SecE Fire Did not ignite

Eastex Products, LLC | 71 Armstrong Road, Plymouth, MA 02360, USA

Confidential – Rev.6.23

Test/Property	Method	Unit/Standard	Results
Cold Crack	ASTM D 2136	Conditioned: -40C for 6 hours	Pass
Colorfastness to Crocking	AATCC 8	Dry Procedure	No change or staining
		Wet Procedure	No change or staining
Heat Test	Samples Placed in Oven	Conditioned: 105 C for 6 hours	No Change to coating or fabric