GRIPGUARD DOTS

GripGuard Dots is an all black laminate that combines abrasion and moisture resistant Nylon 1000D with a Slip-Not Dots backing for durable, dependable grip in wet or dry conditions.

KEY FEATURES

Dual-Surface Construction
Nylon 1000D for structure and Slip-Not Dots 12000 for secure, non-skid grip

Non-Slip Backing
Improves grip and stability by creating a textured surface that reduces shifting and sliding

Moisture Resistant
PU coating and DWR finish help repel water and protect against moisture exposure

Abrasion Resistant
Maintains surface integrity and performance even under frequent friction

APPLICATIONS

Seating
Durable seating surfaces and protective seat panels for high-wear environments

Tactical
Packs, pouches, equipment panels, and gear requiring secure grip

Marine
Moisture-resistant seating panels and protective covers

Industrial
Equipment covers, tool organizers, and protective work surfaces

SPECIFICATIONS

Composition
60% PVC, 30% 1000D Nylon, 10% Polyester

Weight
1235 gsm (± 5%)

Width
54" (± 0.5")

Thickness
1.4mm (± 0.5mm)

Color/SKU
Black/60155



PERFORMANCE PROPERTIES

Property	Method	Unit/Standard	Result
Tensile Strength*	ASTM D5034-21	lbf	Warp: 681.2 Weft: 549.6
Tearing Strength*	ASTM D2261-13	lbf	Warp: 43.5 Weft: 48.9
Abrasion	ASTM D4966	cycles	100,000+
Coefficient of Friction	ASTM D1894	Static Coefficient (μs) Kinetic Coefficient (μk)	1.430 1.512
Bond Strength*	AATCC 136-2013	lbf	7.2
Elongation Ratio*	ASTM D5034-21	%	Warp: 49.2 Weft: 55.5
Crocking*	AATCC 8	Grade 4 min	Face - Dry: 5 Wet: 5 Back - Dry: 5 Wet: 5
Flammability	CAL TB117-2013	Pass/Fail	Pass

* Disclaimer: Results are based on in-house testing by Eastex Products and are provided for reference only; results have not been independently certified and may vary.

Proprietary information of Eastex Products, LLC. Not to be shared or distributed without permission.